Order Form



1. Base							hup! Base DPC to ground level
Are you using the hup!	Base?	Yes	No				dimension required
lf yes, please answer tl	ne questions b	elow:					
What height is the bas	e DPC to grou	nd?					Base DPC is usually 22mm below the back door cill if aligning floor
Which foundations will	you be using?	Pads	C	Ground screws			levels with the house.
Which skirt finish do ye	ou require?	Plain	Brick slip:	s (brick type)			La construction a la construction de
If you would like brick	slips, please le	t us know t	he brick ty	pe and mortar co	olour.		12462401012424060
Brick type	Red Multi	Smooth Ar	nthracite	Smooth Red	Rustic Buff Multi		h 1
Mortar colour	Grey	Sand	Red				
Intrusions needed (ple	ase mark on th	ne base plai	n below)	Drain cover	Obstruction	Drain Pipes	

Please draw the footprint of your building marking each elevation A, B, C, D etc. If you are using full height walls from base, you should use the base datum which lines up with the external of the Ultrapanel clips - wall finishes and battens will overhang the base. If you are using hup! on existing walls, please complete the below details. See specification guide for more details.

hup! on existing wall

Is hup! going on a existing wall? Yes

What is the thickness of existing wall? mm

Do you want it on cill or full clad? Cill (use internal frame dimension) Full Clad (use external base dimension)

If on cill, please send over ONLY the internal frame dimension. If using full clad, please send over ONLY the external base dimensions.

No

-	· · · · ·		 										-		

Extended Base Tray required?

Width of Cavity wall 300mm. See hup! Specification Guide for more details.

Please note hup! walls will protrude at least 45mm (25mm for battens, plus c15mm depending on claddings) outside of your base so that the wall finishes (claddings) will be ventilated. All critical dimensions will be confirmed before order stage.

Order Form



2. Elevations

Please draw each elevation of your hup! walls marking the elevations clearly with A, B, C, D etc. Include window and doors sizes and distance from the eaves as well as the floor clearly.

Tick this box if you require the cable management panel which is supplied on all panels above 560mm.

													 		_			
															_			

Order Form



						 		_					 			_	

3. Wall Finishes

Depending on the wall finish can change the sequence of the battens and calcium silicate board, please tick the wall finish for this project?

D del March		Decide	
Brick Mesh	Brick Slips	Render	External Cladding - Type

4. Walling kit

Please tick the box to confirm which elements of the walling kit you will require to be supplied by Ultraframe.

None - I am supplying my own Ventilation trim only Aperture trim only Batten kit (includes battens and fixings) Render Board kit (includes ventilation trim, aperture trims and battens) Brick Mesh (includes trims, battens and render board)	Brick Mesh Specification: Grey Brick/Medium mortar Multi Buff/Medium mortar Warm Buff/Medium mortar Terracotta/Medium mortar Multi Red/Medium mortar Mult Orange/Medium mortar		Multi Buff/Light mortar Warm Buff/Light mortar Terracotta/Light mortar Multi Red/Light mortar Mult Orange/Light mortar Grey Brick/Grey mortar
render board) 5. Aperture Trim Colour	Grey Brick/Light mortar		
White Smooth Grey	Light Oak	Rosewood	

Surveyor's Details

For the next 6 months, we will discuss every hup! order with the surveyor to ensure that it has been specified correctly, and therefore, avoid any potential errors on site. Please include your surveyor's details below.

NAME:

CONTACT NO: